Borehole and crack fillers

Technical information sheet

350g / Item no.101421 / EAN 4016215101421

Ideal for quickly repairing drill holes, small cracks and similar damaged areas indoors and in damp rooms. Thanks to the ready-to-use application directly from the tube, no mixing is required. Can be applied cleanly and precisely, dries reliably and forms a smooth surface - perfect for quick repairs and optimum preparation for subsequent paints or coatings.

- For quickly repairing dowel holes and small cracks in interior areas
- directly from the tube into the drill hole
- extra white
- Quick drying
- Also for damp rooms

Area of application

Repair filler from the tube for drill holes and cracks. For indoors and damp rooms, on plaster, concrete, masonry, woodchip and paintwork.

Preparation

The substrate must be dry, stable and free of dust and grease. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF.

Processing

Knead the tube thoroughly before use. Squeeze the filler directly from the tube onto the damaged area and smooth it out or create a texture as desired. Maximum layer thickness: 5 mm. If necessary, apply a second coat once dry. Clean tools with water immediately after use.

Storage

Keep the tube tightly closed, childproof and store in a cool but frost-free place.

Notes

Application temperature:
+5 °C for the material, ambient air and substrate

Please refer to the safety data sheet for safety-related information. You can obtain the latest safety data sheets from our website www.baufan.de.

Disposal:
Only send completely empty containers for recycling. Dried-out material residues may be disposed of as household waste or as construction site waste. Dispose of uncured residues in accordance with waste code No. 08 04 10.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.