Wood Repair

Technical information sheet

400g / Item no.101025 / EAN 4016215101025

The ready-to-use wood repair is a light brown dispersion-based levelling compound with a high filling capacity. It is clean and easy to apply, hardens without cracking and remains slightly flexible to compensate for natural wood movement. Ideal for repairs to wood indoors and - with a suitable coat - also outdoors.

- Light brown filler for repairing cracks, holes and imperfections
- High filling capacity
- hardens without cracking
- paintable
- Can be used indoors and also outdoors with a weather-resistant top coat

Area of application

Wood filler for filling and smoothing cracks, holes and edges. Flexible after curing, for indoors and outdoors with weatherproof coating. Professional quality.

Preparation

For wooden surfaces. The substrate must be clean, sound and free of separating agents. Weathered wood must be removed down to the sound layer.

Processing

Knead the tube well before use. Press the filler directly into the area to be repaired and smooth with a spatula. This product can be applied in one coat up to a thickness of 5 mm. For deeper holes, a further coat can be applied after the first coat has dried completely. Once fully cured, the filler can be painted with all water-based paints and varnishes. When used outdoors, a weather-resistant top coat must be applied after full drying. Clean tools with water immediately after use. Drying time: approx. 12 hours (depending on layer thickness) under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions. Tinting: With universal tinting concentrates.

Consumption

Per mm application thickness → approx. 1.8 kg/m²

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.