Woodchip Repair Filler

Technical information sheet

330g / Item no.020425 / EAN 4016215020425

The clean and quick solution for damaged woodchip wallpaper. Ideal for repairing cracks, dowel holes and similar damaged areas. The filler is solvent-free, easy to apply, easy to model and quick-drying. Thanks to its structure, it adapts excellently to the rough fibre grain.

- White textured filler
- Adapts optimally to the coarse fibre grain size
- easy to model
- Quick drying
- paintable
- solvent-free

Area of application

Repair filler for woodchip fibre for repairing dowel holes, cracks and damaged areas. Structure adapts ideally to the woodchip fibre grain. For interior use.

Preparation

The substrate must be dry, clean, sound and free of dust and grease. Remove loose material from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Pre-fill deep holes and break-outs with baufan interior filler or baufan surface filler. Glue open seams of woodchip wallpaper with baufan Seam Adhesive. Not suitable for filling work on wood, metal, glass and plastic.

Processing

Knead the tube well before use and apply a spatula directly from the tube to the damaged area and, if necessary, give the desired surface structure with a spatula or brush. Once dry, the filled surface can be painted over. Clean tools with water immediately after use. Drying time: approx. 1 hour under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture: see batch label.

Notes

Application temperature: +5 °C to +30 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.