



White, highly opaque marking paint for direct application on sports fields and lawns. Sprayable, quick-drying and rain-resistant for permanently visible lines. Adheres reliably even on slightly damp grass and ensures even, professional markings. Ideal for training and playing surfaces as well as temporary line markings in the sports and leisure sector.

- Pure white, highly opaque marking paint
- for the temporary marking of sports fields and lawns
- Suitable for all common marking devices
- solvent-free
- Quick drying
- rain resistant
- Adjustable for spraying

### Area of application

Line marking paint for sports fields, natural turf and hard pitches. Very good adhesion on dry grass and good visibility even in the rain.

### Preparation

For natural grass surfaces, sports fields and hard courts (tennis courts). The areas to be sprayed must be dry. The grass should be cut as short as possible.

### Processing

Do not mix baufan Sportplatzmarkierung Direct with other colours. The colour is ready to use. Stir well before use. Apply undiluted with appropriate marking equipment using the pressure spraying method. Clean the marking trolley/spraying nozzle carefully with clear water immediately after use (spray until the water runs clear). Drying time: approx. 2-5 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); in unfavourable conditions, the drying time is correspondingly longer. Tinting: With universal tinting concentrates or full-tone and tinting paint.

### Consumption

per square → approx. 6.0 - 10.0 litres (empirical values for 10 cm width) Decisive for the consumption are the condition of the floor and the working method of the user.

### Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

### Notes

Processing temperature: +5 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. Wear safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. Hazardous respirable droplets may be produced when spraying. Do not inhale aerosol or mist. Use combination filter A2/P2 when spraying.

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.