Glassfibre and Wall Covering Adhesive

Technical information sheet

750g / Item no.102664 / EAN 4016215102664
3kg / Item no.102626 / EAN 4016215102626
16kg / Item no.102633 / EAN 4016215102633

For the secure and durable bonding of glass fibre fabric, non-woven paint and heavy wall coverings such as vinyl or textile wallpaper indoors. The high-performance special adhesive can be applied evenly and dries transparently. Ideal for professional applications, it ensures bubble-free results and a stable base for subsequent painting or renovation work.

- Extra strong adhesive strength
- For glass fibre fabric, painter's fleece and heavy wall coverings
- Very high moisture resistance when painted over
- dries transparent
- solvent-free

Area of application

Paste for glass fibre fabric, wall and ceiling coverings as well as textile, cork and PVC wallpapers. Also suitable as an adhesion booster for wallpaper adhesives indoors

Preparation

Suitable substrates - concrete, aerated concrete, gypsum wallboards, levelling compounds, cement and gypsum plasters, rigid foam and wood-based panels, old emulsion and sanded paint coats. The substrate must be dry, clean, sound, evenly absorbent and free of dust and grease. Remove loose material, old wallpaper and poorly adhering coats of paint from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. If in doubt, carry out a test application. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

Processing

Stir the adhesive well before use. Cut the glass fibre fabric or wallpaper to the appropriate length. Apply the adhesive generously and evenly to the wall with a lambskin roller in 1 - 3 widths and allow to flash off for a few minutes. Finally, apply the wallpaper to the wall using a hard rubber roller without leaving any bubbles. In the case of slightly absorbent substrates, low temperatures or high humidity, allow a slightly longer flash-off time. Please observe the wall covering manufacturer's processing guidelines for all work. Remove adhesive residues immediately with clean water. Clean tools with water immediately after use. The wall and ceiling surfaces can be painted over with suitable emulsion paints. The application time is approx. 20 minutes. The wall covering can still be corrected within a maximum of 15 minutes if necessary. Drying time Can be painted over after approx. 24 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); in unfavourable conditions, the drying time is correspondingly longer.

Consumption

Smooth surfaces → from 200 g/m² Determine exact consumption quantity by applying a test coat to the object.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking while using the adhesive. Wear safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.