Mounting adhesive express

Technical information sheet

280ml / Item no.102695 / EAN 4016215102695

White, solvent-free power adhesive for secure bonding to wood, concrete, plaster and similar substrates. For wood, PVC and carpet mouldings, PVC cable ducts, wood panelling, door frames, decorative profiles made of rigid foam, ceramic tiles, etc. Not suitable for permanent wet exposure.

- Secure fastening without nails and screws
- for skirting boards, decorative profiles, etc.
- inside and outside
- Once cured, it is temperature-resistant from -20 °C to +70 °C

Area of application

A versatile, solvent-free high-strength adhesive. Ideal for bonding skirting boards, cable ducts, decorative mouldings and ceramic tiles.

Preparation

The surfaces to be bonded must be dry, firm, dust-free and grease-free. At least one of the surfaces must be absorbent. Prime highly absorbent, sanding or chalking substrates with Deep Primer LF.

Processing

Cut off the tip of the cartridge just above the thread and screw on the nozzle. Apply the adhesive in dots or beads. Join the parts together and press them firmly into place. Secure heavy parts or rigid strips until the adhesive has set. Remove any adhesive residue immediately with water.

Drying time:
Fully cured and load-bearing after 24–72 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); drying time will be correspondingly longer under unfavourable conditions.

Storage

Store the container tightly sealed in a cool place, but away from frost.

Notes

Application temperature:
Do not apply when the surface or ambient temperature is below +5 °C.

Keep out of the reach of children. In case of contact with the eyes or skin, rinse immediately and thoroughly with water. Do not allow the product to enter the drainage system, watercourses or the ground.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website at www.baufan.de.

Disposal:
Only send completely empty containers for recycling. Dried-out material residues may be disposed of as household waste or as construction site waste. Dispose of uncured residues in accordance with EWC waste code No. 08 04 10.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Phone +49 (0)341 44655-0 ■ E-mail info@baufan.de ■ Internet www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.