

# Roller Adhesive for non-woven wallpapers PREMIUM

## Technical information sheet

200g / Item no.102367 / EAN 4016215102367



High-quality, fast-dissolving methylcellulose paste. Ideal for pasting non-woven wallpaper by applying paste to the wall or for traditional paste application to the wallpaper.

- For smooth and embossed non-woven wallpapers and non-woven woodchip fibre
- with the roll directly onto the wall
- Does not splash or drip
- with powerful methyl cellulose, synthetic resin and adhesive strength enhancers
- instant - ready to use in 5 minutes
- High initial adhesion and bonding strength
- Easily correctable
- dries transparent
- free from preservatives

### Area of application

Non-woven wallpaper paste for wall pasting technique and classic application. Ideal for non-woven, vinyl, embossed, textile and glass fibre wallpapers, extra strong.

### Preparation

The substrate must be dry, sound and free of separating agents (grease, dust, formwork oil, etc.). Remove old, poorly adhering wallpaper and distemper with baufan wallpaper stripper. Repair cracks and holes with baufan interior filler or decumur super adhesive filler. Pre-treat highly absorbent, sanding and chalking substrates with baufan Deep Penetrating Primer LF. For translucent wallpapers (especially on substrates of different colours), we recommend a primer coat of baufan Wallpaper Primer White.

### Processing

Application ratio: Application to the substrate (non-woven wallpaper / poly-laminated glass fibre wallpaper): 1:15 = 3.0 litres of water = 15-20 m<sup>2</sup> Application to the wallpaper (vinyl wallpaper / heavy wallpaper; fabric / textile wallpaper): 1:20 = 4 litres of water = 20-25 m<sup>2</sup> Add baufan Roll-Kleister quickly and quickly to cold water while stirring vigorously and continue stirring for a short time. Stir again vigorously after 5 minutes. Application to the substrate: As non-woven wallpapers do not require a soaking time, they can be applied quickly and easily using the wall pasting technique. To do this, apply the mixed paste evenly to the substrate with a short-pile roller or brush in the width of 1 - 2 wallpaper strips. Lay the wallpaper sheet directly into the fresh paste bed and press down evenly and bubble-free. When applying to the wallpaper: Spread the wallpaper evenly with paste and lay together. After sufficient soaking time, apply the wallpapers butt-jointed and press down. The wallpaper manufacturer's instructions must be observed. Remove any paste residue on the front of the wallpaper immediately with a damp cloth.

### Consumption

200 - 300 ml/m<sup>2</sup>

### Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

### Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking during use. In case of contact with

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

**Note:**

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.