



Wallpaper Seam Adhesive

Technical information sheet

60g / Item no.102657 / EAN 4016215102657



Ready-to-use dispersion adhesive for re-gluing open wallpaper seams on all substrates. Also ideal for critical areas - e.g. on window frames and in radiator niches.

- for re-gluing open wallpaper seams on all substrates
- Ideal for critical areas such as window frames and radiator niches
- High adhesive strength
- for all wallpapers
- solvent-free

Area of application

Ready-to-use dispersion adhesive is suitable for re-gluing detached (burst) seams of wallpaper on all substrates.

Preparation

The substrate must be stable and free of dust.

Processing

Knead the tube well before use. Apply the adhesive directly from the tube to the wallpaper or substrate, spread evenly and press the loose wallpaper into place. Remove adhesive residue immediately with a damp cloth. Clean tools with water after use. Drying time: approx. 10-15 minutes under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate. Keep out of reach of children. Ensure adequate ventilation during processing and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.